

ANYCERT-SAA-AS/NZS 5000.2-450/750V-SDI-D

Single Core Double Insulation Electric Wire



页码

应用

- Suitable for switch gear and control panel wiring. It is also used for other fixed wiring in protected duct slots, such as construction and the installation of movable houses and caravans.

结构

- 符合 AS/NZS1125 标准导体, 1 类, 2 类或 5 类铜丝
- 符合 AS/NZS 3808 标准绝缘, PVC V90
- 符合 AS/NZS 3808 标准加强外绝缘, PVC 5V-90

特点

- Environmentally protect materials, no harmful substances, in compliance with RoHS or REACH directives.
- Double insulation make the wire more protect.

性能

- Operating voltage: 450/750V
- Minimum bending radius:
Mobile installation: 15x cable OD
Fixed installation: 4x cable OD
- Operating temperature range:
Mobile installation: -5° C to +90° C
Fixed installation: -40° C to +90° C
- Flame retardant and flame retardant: IEC 60332.1

Type	Core*size	O.D.	Weight
5000.2SDID	1×1.0	4.1	25.5
5000.2SDID	1×1.5	4.4	31.8
5000.2SDID	1×2.5	5	45.3
5000.2SDID	1×4	6	67.7
5000.2SDID	1×6	6.5	89.3
5000.2SDID	1×10	7.8	138.3
5000.2SDID	1×16	9.1	204.8

*Customized cable acceptable.