

ANYCOMPLEX- YFFB (300/500V)

Flex Flat Track Cable YFFB

ANYTE CABLE



应用

- Power, control and connection cables for drive systems . fixed installations and for occasional movements without forced force in a fixed direction. Suitable for indoor use.

结构

- Conductor: Multiple strands of fine oxygen-free
- bare copper wire, class 5
 - Insulation: special PVC mix
 - Core identification: colored or numbered, ground wire in yellow/green (optional)
 - Core line structure: in a line or flower shaped.
 - Shielding :braided copper wire shield (optional)
 - Sheathing material: special PVC mix
 - Sheath color: black or gray (can be customized)

特点

- No hazardous substances, RoHS or REACH compliant
- Conforms to CE/TUV standards, etc.
- Tensile strength, tear resistance, flexibility, good performance and stability

性能

- Operating voltage: 300/500V
- Minimum bending radius:
 - mobile installation: 10x cable OD
 - Operating temperature range:
 - mobile installation: -5° C to +70° C

| Type | Cores*size | O. D. | weight |
|------|------------|----------|--------|
| YFFB | 3×0.75 | 10.1×4.7 | 82.5 |
| YFFB | 4×0.75 | 14.8×4.7 | 118.8 |
| YFFB | 5×0.75 | 17.1×4.7 | 139.2 |
| YFFB | 6×0.75 | 19.4×4.7 | 159.7 |
| YFFB | 9×0.75 | 26.3×4.7 | 221.2 |
| YFFB | 10×0.75 | 28.6×4.7 | 241.6 |
| YFFB | 12×0.75 | 34.4×4.7 | 290.5 |
| YFFB | 16×0.75 | 43.6×4.7 | 372.4 |
| YFFB | 18×0.75 | 48.2×4.7 | 413.4 |
| YFFB | 20×0.75 | 30.4×8.6 | 473.8 |
| YFFB | 24×0.75 | 33.2×9.3 | 560.5 |
| YFFB | 30×0.75 | 42.9×8.6 | 677.0 |
| YFFB | 36×0.75 | 47×9.3 | 804.4 |
| YFFB | 40×0.75 | 55.3×8.6 | 880.2 |
| YFFB | 48×0.75 | 60.8×9.3 | 1048.2 |
| YFFB | 54×0.75 | 67.7×9.3 | 1170.1 |
| YFFB | 60×0.75 | 74.6×9.3 | 1292.0 |
| YFFB | 3×1 | 11.4×5.4 | 106.4 |
| YFFB | 4×1 | 16.8×5.4 | 154.0 |

| Type | Cores*size | O. D. | weight |
|------|------------|-----------|--------|
| YFFB | 5×1 | 19.4×5.4 | 180.4 |
| YFFB | 6×1 | 22×5.4 | 206.8 |
| YFFB | 9×1 | 29.8×5.4 | 286.0 |
| YFFB | 10×1 | 32.4×5.4 | 312.4 |
| YFFB | 12×1 | 39×5.4 | 375.8 |
| YFFB | 16×1 | 49.4×5.4 | 481.4 |
| YFFB | 18×1 | 54.6×5.4 | 534.2 |
| YFFB | 20×1 | 34.5×9.8 | 609.0 |
| YFFB | 24×1 | 37.6×10.6 | 719.9 |
| YFFB | 30×1 | 48.5×9.8 | 869.4 |
| YFFB | 36×1 | 53.2×10.6 | 1032.3 |
| YFFB | 40×1 | 62.6×9.8 | 1129.9 |
| YFFB | 48×1 | 68.8×10.6 | 1344.8 |
| YFFB | 54×1 | 76.6×10.6 | 1501.0 |
| YFFB | 60×1 | 84.4×10.6 | 1657.3 |
| YFFB | 3×1.5 | 12.9×5.9 | 137.1 |
| YFFB | 4×1.5 | 18.8×5.9 | 196.0 |
| YFFB | 5×1.5 | 21.9×5.9 | 231.8 |
| YFFB | 6×1.5 | 25×5.9 | 267.5 |