

ANYCERT-UL/CUL/CSA-UL 1095

UL 1095 PVC Electric wire



应用

- This product is used for the connection of UL series rated voltage below 300V, electrical and electronic, instrumentation, machinery and electronic equipment, home appliances power and signal devices or building interior.

Use standard thickness, easy to peel and cut

- With anti-acid, oil, moisture, mildew, environmental protection and other characteristics
- The multi-standard wiring cable UL-CSA and other approvals comply with US and Canadian standards, enabling the cable to be used in the North American market at the same time

结构

- Single or multiple strands of fine stranded 30-16AWG bare copper wire or tinned copper wire
- PVC compound insulation (color can be customized according to customer requirements)

- Rated temperature 80 °C
- Working voltage: 300V
- Oil resistance, flame retardant: CSA FT1 and UL VW-1

页码

Item	Conductor type	Conductor			Insulation		Maximum conductor Resistance 20°C	Minimum insulation resistance	voltage
		size	Wire number	Wire O.D.	Thickness	O.D.			
		AWG	No./mm	mm	mm	mm	Ω/km	MΩ.Km	V
1001109530	Stranded conductor	32	7/0.1	0.30	0.30	0.98	354.24	15	2000
1001109528		30	7/0.127	0.38	0.30	1.06	223.75		
1001109526		28	7/0.16	0.48	0.30	1.16	139.73		
1001109524		26	11/0.16	0.61	0.30	1.29	93.3		
1001109522		24	17/0.16	0.76	0.30	1.44	55.0		
1001109520		22	26/0.16	0.94	0.30	1.62	34.6		
1001109518		20	41/0.16	1.49	0.30	1.86	21.8		
1001109516		18	26/0.254	0.32	0.30	2.20	13.7		
10011095028S1	Solid conductor	28	1/0.32	0.404	0.30	1.0	227.39		
10011095026S1		26	1/0.404	0.511	0.30	1.08	142.79		
10011095024S1		24	110.511	0.643	0.30	1.19	89.39		
10011095022S1		22	1/0.643	0.813	0.30	1.32	54.3		
10011095020S1		20	1/0.813	1.024	0.30	1.49	33.9		
10011095018S1		18	1/1.024	1.29	0.30	1.70	21.4		
10011095016S1		16	1/1.29	0.30	0.30	1.97	13.5		

*customized cable acceptable