

# ANYCERT-UL/CUL/CSA-UL 2725

## UL 2725 multi core computer cable



### 应用

● This product is used for UL series rated voltage below 30V, electrical and electronic, instrumentation, machinery and electronic equipment, home appliances power and signal device or building internal connection, the product has a certain heat resistance, the conductor can work for 60 °C, can work at 60 °C under the environment exposed to solvents such as oil.

- Rated temperature: 60 °C or 80 °C
- Working voltage: 30V
- Oil resistance, flame retardant: CSA FT1 and UL VW-1

### 结构

- Stranded strands of fine bare copper wire conductors
- PVC or SRPVC mixed core wire insulation (color can be customized according to customer requirements)
- Stranded composite cable  
100% coverage of special aluminum foil Mylar tape
- \* (Tinned) copper wire shield braided or wound, coverage rate up to 85%  
PVC mixture outer sheath (color can be customized according to customer requirements)  
\* mark for optional structure

页码

Item	conductor			Insulation			Spiral shield		Jacket		Max. conductor Resistant	Min. insulation resistant	Vol. Res
	size	Wire	O.D.	Cores	thick	O.D.	wire	O.D.	thick	O.D.			
	AWG	No./mm	mm	No	mm	mm	mm	mm	mm	mm	Ω/km	MΩ.km	V
10012725002030	30	7/0.10	0.80	2	0.25	0.8	0.10	1.80	0.38	2.60	354.24	10	500
1001272500330				3				1.92		2.72			
1001272500430				4				2.13		2.93			
1001272500530				5				2.36		3.16			
1001272500228	28	7/0.127	0.88	2	0.25	0.88	0.10	1.96	0.38	2.72	223.75	10	500
1001272500328				3				2.10		2.90			
1001272500428				4				2.32		3.12			
1001272500528				5				2.58		3.41			
1001272500226	26	7/0.16	0.98	2	0.25	0.98	0.12	2.20	0.38	3.00	139.73	10	500
1001272500326				3				2.35		3.15			
1001272500426				4				2.61		3.41			
1001272500526				5				2.89		3.70			