

ANYDATA-AUDIO CABLE

Audio Cable



应用



power cord for connect the audio and multimedia device .

结构

Conductor: stranded fine bare copper or tinned copper wire comply with VDE0295/IEC228

Insulation: PVC mixture material (color can be customized according to customer requirements)

特点

Use environmentally materials, comply with ROHS directive

This product complies with the provisions of the EEC directive 73/23 (low-voltage procedures) of CE

UL VW-1 & CSA FT1 vertical flame test

性能

Operating voltage: 300 V

Insulation resistance: > 10 GOhm x cm in

Operating temperature range:

Movable Installation: - 5 ° C to +70 ° C fixed installation: -40 ° C to +70 ° C

Part No.	size	Sq mm	conductor	O.D. mm
----------	------	-------	-----------	---------

050AUDIO0	0Gauge	53.16	19*39/0.3	15.0
050AUDIO0S		53.42	7*7*61/0.15	
050AUDIO2	2 Gauge	33.62	19*56/0.2	12.0
050AUDIO2S		33.58	7*7*38/0.15	
050AUDIO4	4 Gauge	21.15	19*39/0.2	10.0
050AUDIO4S		21	7*7*38/0.12	
050AUDIO6	6 Gauge	13.29	7*60/0.2	7.80
050AUDIO6S		13	7*7*24/0.12	
050AUDIO8	8 Gauge	8.31	7*37/0.2	6.70
050AUDIO8S		8.36	7*105/0.12	
050AUDIO10	10 Gauge	5.22	7*23/0.2	5.50
050AUDIO10S		5.26	7*66/0.12	
050AUDIO12	12 Gauge	3.31	7*26/0.15	4.50
050AUDIO12S		3.30	7*42/0.12	
050AUDIO14	14 Gauge	2.08	7*16/0.15	3.50
050AUDIO14S		2.00	7*26/0.12	
050AUDIO16	16 Gauge	1.31	7*16/0.15	3.20
050AUDIO16S		1.30	7*16/0.12	
050AUDIO18	18 Gauge	0.823	46*0.15	2.50
050AUDIO18S		0.81	71*0.12	
050AUDIO20	20 Gauge	0.519	30*0.15	2.20
050AUDIO22	22 Gauge	0.32	17*0.15	2.00
050AUDIO24	24 Gauge	0.204	11*0.15	1.80

✘Can produce special cables as customer's request