


# ANYCERT-SAA-AS/NZS 3191-250/440V

## Multi cores PVC Flexible Communication Cable



页码

### 应用

- Suitable for communication, audio, broadcasting, audio systems, burglar alarm systems, intelligent automation systems, automatic meter reading systems, fire protection systems and other transmission data cables that require anti-interference line connections, efficient and safe.

### 结构

- Conductor according to AS/NZS1125, copper wire class 5
  - Insulated to AS/NZS 3808, PVC V90
  - Shielded weave (tinned) copper wire with 85% coverage
- Conforms to AS/NZS 3808 standard sheath, PVC 5V-90

Flame retardant and flame retardant: IEC 60332. 1.  
Operating voltage: 250/440V

### 特点

- Environmentally friendly materials, no harmful substances, in compliance with RoHS or REACH directives
- SAA certified cable for use in Australia, New Zealand, with better electromagnetic compatibility characteristics.

### 性能

- Minimum bending radius:
- Mobile installation: 15x cable OD  
Fixed installation: 4x cable OD
- Operating temperature range:  
Mobile installation: -5° C to +90° C  
Fixed installation: -40° C to +90° C

Type	Core*size	O.D.	Weight
3191RP	2×0.75	7.1	70.7
3191RP	3×0.75	7.4	85.1
3191RP	4×0.75	8.0	101.4
3191RP	5×0.75	8.9	123.5
3191RP	2×1.0	7.5	77.6
3191RP	3×1.0	7.9	94.9
3191RP	4×1.0	8.7	117.7
3191RP	5×1.0	9.4	139.4
3191RP	2×1.5	8.5	94.2
3191RP	3×1.5	9.1	122.0
3191RP	4×1.5	10.1	152.7

Type	Core*size	O.D.	Weight
3191RP	5×1.5	11.2	186.6
3191RP	2×2.5	10.1	130.0
3191RP	3×2.5	10.8	171.0
3191RP	4×2.5	11.8	210.7
3191RP	5×2.5	13.0	258.2
3191RP	2×4.0	11.3	166.2
3191RP	3×4.0	12.1	223.7
3191RP	4×4.0	13.2	279.5
3191RP	5×4.0	14.8	350.3

\*customized cable acceptable