


ANYCERT-SAA-AS/NZS 5000.2-450/750V-TPS

多芯聚氯乙烯扁电线



页码

应用

- Suitable for use in domestic, commercial and industrial direct buried or underground pipelines, without damage to conductors and PVC. Particularly suitable for export to Australia for internal installation in mobile homes, containers, refrigerated cabinets and caravans.

结构

- Conductor, Class 1, Class 2 or Class 5 copper wire
- according to AS/NZS1125
- Insulated to AS/NZS 3808, PVC V90
AS/NZS 3808 standard sheath, PVC 3V-90
Flat, grooved exterior

特点

- Environmentally protect materials, no harmful substances, in compliance with RoHS or REACH.

性能

- Operating voltage: 450/750V
- Minimum bending radius:
Mobile installation: 15x cable OD
Fixed installation: 4x cable OD
- Operating temperature range:
Mobile installation: -5° C to +90° C
Fixed installation: -40° C to +90° C

Type	Core*size	O.D.	Weight
5000.2TPS	2×1.0	6.8×4.3	55.0
5000.2TPS	3×1.0	9.3×4.3	77.1
5000.2TPS	2×1.5	7.4×4.6	68.7
5000.2TPS	3×1.5	10.2×4.6	97.3
5000.2TPS	2×2.5	8.8×5.4	102.2
5000.2TPS	3×2.5	12.2×5.4	145.8
5000.2TPS	2×4	10.6×6.4	151.3
5000.2TPS	3×4	14.8×6.4	217.1
5000.2TPS	2×6	11.6×6.9	197.7
5000.2TPS	3×6	16.3×6.9	286
5000.2TPS	2×10	14.4×8.4	312.2
5000.2TPS	3×10	20.4×8.4	454.2
5000.2TPS	2×16	16.8×9.7	455.8
5000.2TPS	3×16	23.9×9.7	666

Flame retardant and flame retardant: IEC 60332.1

*Customized cable acceptable.