

# ANYDATA-SPEAKER CABLE

## Transparent or Red and Black Speaker Cable



### 应用



For audio transmission occasions.

### 结构

Conductor: stranded fine bare copper or tinned copper wire comply with VDE0295/IEC228

Insulation: PVC mixture material

### 特点

PVC insulated, low loss, high-fidelity, bass, wide dynamic range

Use of high-quality PVC insulation, resistance to wear and good flexibility, anti-clutter signal the outside world and EMI interference

Non-hazardous substances, RoHS compliant

This product complies with the provisions of the EEC directive 73/23 (low-voltage procedures) of CE

Comply with the CE / TUV / VDE standards

### 性能

Operating voltage: 300 V

Insulation resistance: > 10 GOhm x cm in

Operating temperature range:

Movable Installation: - 5 ° C to +70 ° C fixed installation: -40 ° C to +70 ° C

Oil resistant, flame retardant, and the extension of flammable: IEC60332.1 / HD 405.2 and CSA FT1

Anti-radiation intensity: up to 80 × 106cJ/kg

| Part No.           | Core No.*sq mm2 | Outer diameter/mm |
|--------------------|-----------------|-------------------|
| 050SPEAKER00206    | 6.0*2C          | 6.0*12.0          |
| 050SPEAKER00204    | 4.0*2C          | 5.0*10.0          |
| 050SPEAKER00202    | 2.0*2C          | 3.5*7.0           |
| 050SPEAKER002015   | 1.5*2C          | 3.2*6.4           |
| 050SPEAKER00201    | 1.0*2C          | 3.0*6.0           |
| 050SPEAKER0020075  | 0.75*2C         | 2.6*5.2           |
| 050SPEAKER0020075A | 0.75*2C         | 2.5*5.0           |
| 050SPEAKER002005   | 0.5*2C          | 2.3*4.6           |
| 050SPEAKER0020035  | 0.35*2C         | 2.2*4.4           |
| 050SPEAKER0020025  | 0.25*2C         | 2.0*4.0           |
| 050SPEAKER0020025  | 0.25*2C         | 1.8*3.6           |
| 050SPEAKER0020012  | 0.12*2C         | 1.6*3.2           |
| 050SPEAKER0020021  | 21.0*2C         | 10.0*20.0         |
| 050SPEAKER0020013  | 13.0*2C         | 7.8*15.6          |
| 050SPEAKER0020075  | 7.5*2C          | 6.5*13.0          |
| 050SPEAKER0020050  | 5.0*2C          | 5.5*11.0          |
| 050SPEAKER0020030  | 3.0*2C          | 5.4*10.8          |
| 050SPEAKER0020025  | 2.5*2C          | 4.0*8.0           |

✘Can produce special cables as customer's request