

ANYCERT-UL/CUL/CSA-UL 2919

UL 2919 low voltage computer cable



应用

- Suitable for monitors, computers or e-commerce equipment.
- Rated temperature: 80 °C
- Working voltage: 30V
- Oil resistance, flame retardant: CSA FT1 and UL VW-1

结构

- Special PEF or SRPVC mixed core wire insulation (color can be customized according to customer requirements)
 - Stranded composite cable
 - * Insulated plastic film coating
 - * Aluminum foil Mylar 100% coated shield
 - Stranded copper wire (tinned) drain wire
 - * Copper wire (tinned) shield braid, coverage rate up to 85%
- PVC mixture outer sheath (color can be customized according to customer requirements)
- ** Optional structure

页码

Item	conductor			Spiral shield		Shield Wire /size	Inner jacket		Drain wire	Out shield	Jacket	
	AW G	No	No. /mm	Thick mm	O. D. m		Wire mm	O. D. m			Thick mm	O. D. mm
10012919003030	30	3	7/0.10	0.50	1.30	39/0.10	0.30	2.10	-	16x8/0.10	0.85	7.40
10012919003030a	30	6	7/0.10	0.26	0.82	-	-	-	-			
10012919002020	20	2	26/0.16	0.26	1.46	-	-	-	-			
10012919003030b	30	3	7/0.10	0.50	1.30	39/0.10	0.30	2.10	7/0.127	16x10/0.12	0.95	7.20
10012919007028	28	7	7/0.127	0.26	0.90	-	-	-	-	16x10/0.12	1.10	8.0
10012919003028	28	3	7/0.127	0.61	1.60	42/0.12	0.35	2.55	7/0.20			
10012919008028	28	8	7/0.127	0.12	0.63	-	-	-	-			
1001291900228	28	2	7/0.127	0.61	1.60	42/0.12	0.35	2.55	7/0.16	16x10/0.12	0.90	7.90
10012919006026	26	6	7/0.16	0.26	1.0	-	-	-	-	16x10/0.12	1.95	7.90
10012919000028	28	4	7/0.127	0.61	1.60	42/0.12	0.35	2.55	7/0.20			
10012919004024	24	3	7/0.2	0.26	1.12	-	-	-	-			
10012919003028a	28	3	7/0.127	0.61	1.60	42/0.12	0.35	2.55	7/0.20	24x10/0.10	0.81	8.0
10012919003024	24	3	7/0.2	0.26	1.12	-	-	-	-			